

HL-4GMVR

GPON Wireless Router 4x Gigabit LAN Port Wi-Fi 802.11ac With VoIP With CATV Overlay



Product Description

HALNy GPON Gateway is an innovative and powerful product for business and residential subscribers.

All products within the GPON family comply with current ITU-T standards for gigabit passive optical networks (GPONs). The solution is designed to optimize the deployment and roll-out of the service provider. **HL-4GMVR** design offers multi-interoperability with several OLT vendors. The ONT/ONU products are tested and have proven interoperability with most major GPON OLT Vendors.

The solution is designed to optimize the deployment and roll-out of the service provider. This includes interoperability GPON ONT with advanced support for L2 VLANs and Multicast IGMP, L3 Routing with NAT, PPPoE, and easy-to-use Provisioning.

HALNy specializes in cost-effective designs and works closely with service providers to improve their business case through a comprehensive range of standard products, supporting the industry's common demands. HALNy also provides custom designs and services to meet unique customer needs.

Housing can be sold with the Operator logo on the top cover.



All specifications are subject to change without notice. The above product picture is a sample for reference and may vary. Please check with your supplier for exact offers. Actual data throughput and Wi-Fi coverage will vary from network conditions and environmental factors, including the volume of network traffic, building material and construction, and network overhead, resulting in lower actual data throughput and wireless coverage. Quoted network speeds and bandwidth based on current IEEE specifications. Actual performance may be affected by network and service provider factors, interface type, and other conditions.



FIBRAIN Sp. z o.o. 36-062 Zaczernie 190F Poland phone e-mail +48 17 866 08 00 sales@halny.com support@halny.com





Hardware Specification

Flash / RAM	128MB / 256MB	Storage Temp.	-10°C~60°C (14F~140F)
CPU	Dual Core 900MHz	Operating Temp.	0°C~45°C (32F~113F)
WAN Port	GPON B+ SC/APC 2.488Gbps Downstream 1.244Gbps Upstream	Operating Humidity	10% ~ 90% (non-condensing)
GPON Tx	0.5 ~ 5 dBm	Power Supply	DC +12V / 1.5A
GPON Rx	-10 ~ -27 dBm	Buttons	ON/OFF Power, WIFI, WPS, Reset
LAN Port	4 x port 10/100/1000BASE-T (RJ-45) Auto-sensing, auto-detection	Dimension (W x D x H)	210 x 150 x 36mm
	MDI/ MDI-X	Operating	802.11b/g/n:2400- 2485MHz
TEL Port	1 x FXS, RJ11	Frequencies	802.11a/n/ac:5150- 5250MHz
RF Port	Bandwidth 45 ~ 863Mhz Output LeveL=> 78dBuV		
WIFI	2x2 802.11ac wave2 867Mbps 2x2 802.11n 300Mbps Antenna Gain 2*5dBi, External Dual Band	Maximum power of the transmitter	2.4 GHz: up to 20 dBm 5 GHz: up to 23 dBm Transmit power control
		LED	POWER, PON, LOS, INTERNET, WLAN 2.4G, WLAN 5G, LAN1- 4, TEL, CATV

Software Specification

GPON	ITU-T G.984.x and G.988 OMCI G.984.4 / G.988 AES / FEC / DBA Dying GASP Multicast GEM	L3 (HGU Mode)	Router / NAT / PAT PPPoE / DHCP Client Static IP DHCP Server IGMP Proxy VPN Pass-through
	Easy to use provisioning for all ONT configuration DOCSIS like provisioning over GPON/EPON TR-069 OMCI, OTT Upgrade DHCP 66/67 XML RestAPI / JSON		UPnP,DMZ / Port Forwarding IPv4 / IPv6 IPv6 Dual Stack, DS-Lite IPv6 Firewall RFC-6092 WAN bridge
		Telephony	SIP, DTMF, Dial Plan
EasyMesh	Controller and Agent	Manage- ment	WEB (two user accounts) Remote Syslog, OMCI

All specifications are subject to change without notice. The above product picture is a sample for reference and may vary. Please check with your supplier for exact offers. Actual data throughput and Wi-Fi coverage will vary from network conditions and environmental factors, including the volume of network traffic, building material and construction, and network overhead, resulting in lower actual data throughput and wireless coverage. Quoted network speeds and bandwidth based on current IEEE specifications. Actual performance may be affected by network and service provider factors, interface type, and other conditions.



FIBRAIN Sp. z o.o. 36-062 Zaczernie 190F Poland phone e-mail +48 17 866 08 00 sales@halny.com support@halny.com






Interoperability Test Result

NOKIA (Alcatel-Lucent)	Cisco/Altice
DZS	FIBERHOME
ZTE	RAISECOM
HUAWEI	ZYXEL
CALIX	ZHONE
ADTRAN	ISKRATEL

rdering Information

HL-4GMVR / HL-4GMVR-EU	HALNY NETWORKS GPON ONT 4-PORT LAN 10/100/1000, 1-PORT RF(CATV), B+ SC/APC, WIFI B/G/N/AC 2.4GHZ/5GHZ N:2X2 300M, AC:2X2 867M WAVE2, 1XPOTS, Router/Bridge, with European Power Adapter
HL-4GMVR-US	HALNY NETWORKS GPON ONT 4-PORT LAN 10/100/1000, 1-PORT RF(CATV), B+ SC/APC, WIFI B/G/N/AC 2.4GHZ/5GHZ N:2X2 300M, AC:2X2 867M WAVE2, 1XPOTS, Router/Bridge, with North America Power Adapter
HL-4GMVR-UK	HALNY NETWORKS GPON ONT 4-PORT LAN 10/100/1000, 1-PORT RF(CATV), B+ SC/APC, WIFI B/G/N/AC 2.4GHZ/5GHZ N:2X2 300M, AC:2X2 867M WAVE2, 1XPOTS, Router/Bridge, with United Kingdom Power Adapter
HL-4GMVR-NOPS	HALNY NETWORKS GPON ONT 4-PORT LAN 10/100/1000, 1-PORT RF(CATV), B+ SC/APC, WIFI B/G/N/AC 2.4GHZ/5GHZ N:2X2 300M, AC:2X2 867M WAVE2, 1XPOTS, Router/Bridge, without Power Adapter Please contact sales for detailed order information





FIBRAIN Sp. z o.o. 36-062 Zaczernie 190F Poland phone e-mail +48 17 866 08 00 sales@halny.com support@halny.com