

# HALNY

High Availability Local Networks

## HL-4GXV-F

**GPON Wireless Router**  
**4x Gigabit LAN Port**  
**Wi-Fi6 AX1800**  
**With VoIP**  
**With mode button**



### Product Description



HALNy GPON Gateway is an innovative and powerful product for business and residential subscribers.

All products within the GPON family comply with current ITU-T standards for gigabit passive optical networks (GPONs). The solution is designed to optimize the deployment and roll-out of the service provider. **HL-4GXV-F** design offers multi-interoperability with several OLT vendors. The ONT/ONU products are tested and have proven interoperability with most major GPON OLT Vendors.

The solution is designed to optimize the deployment and roll-out of the service provider. This includes interoperability GPON ONT with advanced support for L2 VLANs and Multicast IGMP, L3 Routing with NAT, PPPoE, and easy-to-use Provisioning.

HALNy specializes in cost-effective designs and works closely with service providers to improve their business case through a comprehensive range of standard products, supporting the industry's common demands. HALNy also provides custom designs and services to meet unique customer needs.

**Housing can be sold with the Operator logo on the top cover.**




All specifications are subject to change without notice. The above product picture is a sample for reference and may vary. Please check with your supplier for exact offers. Actual data throughput and Wi-Fi coverage will vary from network conditions and environmental factors, including the volume of network traffic, building material and construction, and network overhead, resulting in lower actual data throughput and wireless coverage. Quoted network speeds and bandwidth based on current IEEE specifications. Actual performance may be affected by network and service provider factors, interface type, and other conditions.

[www.halny.com](http://www.halny.com)

FIBRAIN Sp. z o.o.  
36-062 Zaczernie 190F  
Poland

phone  
e-mail

+48 17 866 08 00  
sales@halny.com  
support@halny.com



## Hardware Specification

<b>Flash / RAM</b>	128MB / 256MB	<b>Storage Temp.</b>	-10°C~60°C (14F~140F)
<b>CPU</b>	Dual Core 900MHz	<b>Operating Temp.</b>	0°C~45°C (32F~113F)
<b>WAN Port</b>	GPON B+ SC/APC 2.488Gbps Downstream 1.244Gbps Upstream	<b>Operating Humidity</b>	10% ~ 90% (non-condensing)
<b>GPON Tx</b>	0.5 ~ 5 dBm	<b>Power Supply</b>	DC +12V / 1.5A
<b>GPON Rx</b>	-10 ~ -27 dBm	<b>Buttons</b>	ON/OFF Power WPS, Reset, Mode
<b>LAN Port</b>	4 x port 10/100/1000BASE-T (RJ-45) Auto-sensing, auto-detection MDI/ MDI-X	<b>Dimension (W x D x H)</b>	225 x 142 x 46mm
<b>TEL Port</b>	1 x FXS, RJ11	<b>Operating Frequencies</b>	802.11b/g/n: 2401-2484 MHz 802.11a/n/ac/ax: 5170-5835 MHz
<b>LED</b>	POWER, PON, LOS, NET WLAN 2.4G, WLAN 5G, WPS. LAN1-4, TEL	<b>Maximum power of the transmitter</b>	2.4 GHz: up to 20 dBm 5 GHz: up to 23 dBm Transmit power control
<b>WIFI</b>	2T2R AX1800 5Ghz MU-MIMO Internal antennas		

## Software Specification

<b>GPON</b>	ITU-T G.984.x and G.988 OMCI G.984.4 / G.988 AES / FEC / DBA Dying GASP Multicast GEM	<b>L3 (HGU Mode)</b>	Router / NAT / PAT PPPoE / DHCP Client Static IP DHCP Server IGMP Proxy VPN Pass-through UPnP DMZ / Port Forwarding IPv4 / IPv6 IPv6 Dual Stack IPv6 DS-Lite IPv6 Firewall RFC-6092 WAN bridge
<b>Provisioning</b>	Easy to use provisioning for all ONT configuration  DOCSIS like provisioning over GPON/EPON TR-069 OMCI OTT Upgrade DHCP 66/67 XML RestAPI / JSON	<b>Telephony</b>	SIP, DTMF, Dial Plan
<b>Management</b>	WEB (two user accounts) Remote Syslog, OMCI	<b>EasyMesh</b>	Controller and Agent

All specifications are subject to change without notice. The above product picture is a sample for reference and may vary. Please check with your supplier for exact offers. Actual data throughput and Wi-Fi coverage will vary from network conditions and environmental factors, including the volume of network traffic, building material and construction, and network overhead, resulting in lower actual data throughput and wireless coverage. Quoted network speeds and bandwidth based on current IEEE specifications. Actual performance may be affected by network and service provider factors, interface type, and other conditions.




## Interoperability Test Result

<b>NOKIA</b> (Alcatel-Lucent)	<b>Cisco/AltiCe</b>
<b>DZS</b>	<b>FIBERHOME</b>
<b>ZTE</b>	<b>RAISECOM</b>
<b>HUAWEI</b>	<b>ZYXEL</b>
<b>CALIX</b>	<b>ZHONE</b>
<b>ADTRAN</b>	<b>ISKRATEL</b>

## Ordering Information

<b>HL-4GXV-F / HL-4GXV-F-EU</b>	HALNY NETWORKS GPON ONT 4-PORT LAN 10/100/1000, B+ SC/APC, WIFI B/G/N/AC/AX 2.4GHZ/5GHZ AX:2X2, 1XPOTS, Router/Bridge, with European Power Adapter
<b>HL-4GXV-F-US</b>	HALNY NETWORKS GPON ONT 4-PORT LAN 10/100/1000, B+ SC/APC, WIFI B/G/N/AC/AX 2.4GHZ/5GHZ AX:2X2, 1XPOTS, Router/Bridge, with North America Power Adapter
<b>HL-4GXV-F-UK</b>	HALNY NETWORKS GPON ONT 4-PORT LAN 10/100/1000, B+ SC/APC, WIFI B/G/N/AC/AX 2.4GHZ/5GHZ AX:2X2, 1XPOTS, Router/Bridge, with United Kingdom Power Adapter
<b>HL-4GXV-F-NOPS</b>	HALNY NETWORKS GPON ONT 4-PORT LAN 10/100/1000, B+ SC/APC, WIFI B/G/N/AC/AX 2.4GHZ/5GHZ AX:2X2, 1XPOTS, Router/Bridge, without Power Adapter
<b>HL-FIBER-TRAY</b>	HALNY TRAY FOR ONT/CPE

Please **contact sales** for detailed order information



All specifications are subject to change without notice. The above product picture is a sample for reference and may vary. Please check with your supplier for exact offers. Actual data throughput and Wi-Fi coverage will vary from network conditions and environmental factors, including the volume of network traffic, building material and construction, and network overhead, resulting in lower actual data throughput and wireless coverage. Quoted network speeds and bandwidth based on current IEEE specifications. Actual performance may be affected by network and service provider factors, interface type, and other conditions.